

(12) **United States Patent**  
Takatori et al.

(10) Patent No.: **US 6,229,855 B1**

(45) Date of Patent: **\*May 8, 2001**

(54) **ADAPTIVE TRANSMITTER FOR DIGITAL TRANSMISSION**

(75) Inventors: **Hiroshi Takatori**, Sacramento, CA (US); **Ahmed F. Shalash**, Minneapolis, MN (US)

(73) Assignees: **ADC Telecommunications, Inc.**, Minneapolis, MN (US); **Level One Communications, Inc.**, Sacramento, CA (US)

(\*) Notice: This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **08/917,632**

(22) Filed: **Aug. 22, 1997**

**Related U.S. Application Data**

(60) Provisional application No. 60/025,344, filed on Sep. 3, 1996.

(51) Int. Cl.<sup>7</sup> ..... **H04K 1/02**

(52) U.S. Cl. .... **375/296; 370/201; 324/628; 455/522**

(58) Field of Search ..... **375/219, 296, 375/285, 257, 287, 288; 370/201, 282, 286; 379/399, 406, 410, 411; 455/500, 501, 127, 67.4, 522, 571, 14, 69, 115, 126; 324/628**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,735,266	• 5/1973	Amitay	.....	370/201
4,087,639	• 5/1978	Beene et al.	.....	370/482
4,450,555	• 5/1984	Pays	.....	370/201
4,648,123	• 3/1987	Schrock	.....	455/69
5,063,351	• 11/1991	Goldthorp et al.	.....	324/628
5,257,283	• 10/1993	Gilhausen et al.	.....	455/522
5,276,918	• 1/1994	Cornforth et al.	.....	455/571
5,313,656	• 5/1994	Vaisanen et al.	.....	455/67.4
5,483,551	• 1/1996	Huang et al.	.....	375/219
5,548,222	• 8/1996	Jensen et al.	.....	324/628
5,731,706	• 3/1998	Koeman et al.	.....	324/628
5,754,943	• 5/1998	Arai et al.	.....	455/14
5,924,043	• 7/1999	Takano	.....	455/522

\* cited by examiner

*Primary Examiner*—Lee Nguyen

*Assistant Examiner*—Conguen Tran

(74) *Attorney, Agent, or Firm*—Merchant & Gould P.C.

(57) **ABSTRACT**

A method for controlling the power and/or frequency output of a digital data network's transmitters is described. The method controls the transmitter power and/or frequency output by using line loss information as well as the noise margin at both the central office and remote site sides of the transmission link. The transmitters are controlled to minimize the crosstalk between the interconnections on the network. Measurements are taken of the cable losses and signal-to-noise ratios present on the system and the transmitter power and/or frequency are adjusted to minimize unwanted interactions between transceiver pairs on the network.

**13 Claims, 4 Drawing Sheets**

